



## TE-W315

### WOVEN GEOTEXTILE

PROPERTY	TEST METHOD	M.A.R.V. (Min. Avg Roll Value)
Weight (Typical)	ASTM D-5261	6.3 oz/yd <sup>2</sup> (214 g/m <sup>2</sup> )
Grab Tensile	ASTM D-4632	315 lbs (1.40 kN)
Grab Elongation	ASTM D-4632	15%
Trapezoid Tear Strength	ASTM D-4533	120 lbs (0.533 kN)
CBRPuncture Resistance	ASTM D-6241	1000 lbs (4.45 kN)
Permittivity*	ASTM D-4491	0.05 sec <sup>-1</sup>
Water Flow*	ASTMD-4491	4 gpm/ft <sup>2</sup> (163 L/min/m <sup>2</sup> )
AOS*	ASTM D-4751	40 US Sieve (0.425 mm)
U.V. Resistance	ASTM D-4355	70%/500 hours

\*At the time of manufacturing. Handling, storage, and shipping may change these properties.

PACKAGING	
Roll Dimensions – (W X L)	12.5 ft x 360 ft 15 x 300 17.5 ft x 258 ft
Square yards per roll	500
Estimated Roll Weight	210 lbs

This data is provided for informational purposes only. *Titan Environmental Containment Ltd.* makes no warranties as to the suitability or the fitness for a specific use or merchantability of the products referred to, no guarantee of satisfactory results from reliance upon contained information or recommendations and disclaims all liability from resulting loss or damage. This information is subject to change without notice, please check with *Titan Environmental Containment Ltd.* for current updates.

**Titan Environmental Containment Ltd.**

777 Quest Blvd, PO Box 9 • Ile des Chenes, Manitoba • R0A0T0 • CANADA

Phone: +1.204.878.3955 Fax: +1.204.878.3980 Toll Free: +1.866.327.1957