

BENTOMAT® & CLAYMAX® PANEL & ROLL SPECIFICATIONS

Panel Specifications

PRODUCTS	DIMENSIONS WIDTH x LENGTH	AREA	EFFECTIVE AREA
BENTOMAT® ST	15 ft x 150 ft (4.6 m x 45.7 m)	2,250 ft ² (209 m ²)	2,145 ft ² (200 m ²)
BENTOMAT SDN	14.5 ft x 150 ft (4.4 m x 45.7 m)	2,175 ft ² (202 m ²)	2,071 ft ² (193 m ²)
BENTOMAT DN	14.5 ft x 150 ft (4.4 m x 45.7 m)	2,175 ft ² (202 m ²)	2,071 ft ² (193 m ²)
BENTOMAT CL	15 ft x 150 ft (4.6 m x 45.7 m)	2,250 ft ² (209 m ²)	2,070 ft ² (193 m ²)
BENTOMAT CLT	15 ft x 150 ft (4.6 m x 45.7 m)	2,250 ft ² (209 m ²)	2,070 ft ² (193 m ²)
BENTOMAT 200R	15 ft x 150 ft (4.6 m x 45.7 m)	2,250 ft ² (209 m ²)	2,145 ft ² (200 m ²)
CLAYMAX 200R (Lovell)	15 ft x 150 ft (4.6 m x 45.7 m)	2,250 ft ² (209 m ²)	2,040 ft ² (190 m ²)

Roll Specifications

PRODUCTS	DIMENSIONS Length x Diameter (Avg.)	NOMINAL WEIGHT	ROLLS / TRUCKLOAD
BENTOMAT ST	16 ft x 24 in (4.9 m x 610 mm)	2,650 lbs (1204 kg)	17 rolls per truckload
BENTOMAT SDN	16 ft x 24 in (4.9 m x 610 mm)	2,650 lbs (1204 kg)	16 rolls per truckload
BENTOMAT DN	16 ft x 24 in (4.9 m x 610 mm)	2,700 lbs (1227 kg)	16 rolls per truckload
BENTOMAT CL	16 ft x 25 in (4.9 m x 635 mm)	2,750 lbs (1250 kg)	15 rolls per truckload
BENTOMAT CLT	16 ft x 26 in (4.9 m x 660 mm)	2,950 lbs (1340 kg)	15 rolls per truckload
BENTOMAT 200R	16 ft x 24 in (4.9 m x 610 mm)	2,650 lbs (1204 kg)	17 rolls per truckload
CLAYMAX 200R (Lovell)	16 ft x 20 in (4.9 m x 510 mm)	3,000 lbs (1363 kg)	15 rolls per truckload

Unloading and handling equipment for all GCL products:

- Spreader bar and core pipe: Spreader bar 17 ft (5.2 m) long; core pipe 20 ft (6.1 m) long, nominal pipe size, XXH.
- A solid 3.5 in. (90 mm) O.D. x 14.5 ft (4.4 m) solid steel pipe stinger attachment for a forklift.
- Slings: 2 Polyester slings are required, approximately 12 ft (3.7 m) long x 2 in (50 mm) wide each.
- Vehicle needed: Front end loader or forklift (are typical).

Standard Roll Specifications:

- Packaging: U.V. resistant polyethylene sleeve.