



TE-C32 BD

EROSION CONTROL BLANKET

The Titan Environmental Containment Erosion Control Blanket TE-C32 BD is a long-term 100% biodegradable double net 100% coconut fiber erosion control blanket designed for use on extreme slope and channel applications requiring erosion control for up to 24 months depending on moisture, light, and environmental conditions. The blanket is sewn together on 1.5 inch (38.1 mm) centers. The TE-C32 BD meets all requirements established in the FHWA FP-03 as a Type 4 erosion control blanket for use on slopes with gradients not exceeding 1:1 (h:v) and has been tested by the National Transportation Product Evaluation Program (NTPEP). The TE-C32 BD comes packaged in clear shrink-wrap with a green band and includes installation instructions.

Product Nomenclature & Properties

- C** = 100% coconut fiber matrix
- 3** = coconut fiber matrix applied at a rate of 0.5 lbs/yd² (270 g/m²)
- 2** = top and bottom leno woven biodegradable nets with a mesh size of 0.5 x 1.0 in (1.3 x 2.54 cm)
- BD** = 100% biodegradable net, thread, and matrix to ensure consistent functional longevity

Index & Bench Scale Testing

Test Description	Test Method	Test Results
Mass per Unit Area	ASTM D6475	9.19 oz/yd ²
Tensile Strength	ASTM D6818	19.9 lb/in @ 9.6% MD 11.9 lb/in @ 15.3% TD
Thickness	ASTM D6525	0.261 in
Light Penetration / Ground Cover	ASTM D6567	12.7% / 87.3%
Water Absorption	ASTM D 1117 & ECTCTASC 00197	271%
Unvegetated Bench-Scale Rain Splash and Runoff (not to be used as a design value)	ASTM D7101	Soil Loss Ratio* = 13.56 Soil Loss Ratio* = 15.10 Soil Loss Ratio* = 16.82
Unvegetated Bench-Scale Shear Stress (not to be used as a design value)	ASTM D7207	2.90 lbs/ft ² @ ½ in. soil loss
Seed Germination and Plant Growth Under Bench-Scale Conditions	ASTM D7322	412% Improvement (increased biomass)

*Soil Loss Ratio = Soil Loss Bare Soil / Soil Loss with RECP = 1 / C-Factor (Note: Soil loss is based on regression analysis)

Design Values

- "C" factor = 0.002
- Maximum Permissible Shear Stress = 2.25 lbs/ft² (108 Pa)
- Maximum Permissible Velocity = 10 ft/sec (3.05 m/s)
- Manning's "n" = 0.03

Standard Roll Details

Width	2.44m (8 ft)	4.88m (16 ft)
Standard Length	34.3m (112.5 ft)	34.3m (112.5 ft)
Area	83.61m ² (100 yd ²)	167.22m ² (200 yd ²)
Weight ± 10%	30.8 kg (68 lb)	61.6 kg (136 lb)

Titan Environmental Containment Ltd.

777 Quest Blvd • Ile des Chenes, Manitoba • R0A0T0 • CANADA
Phone: +1.204.878.3955 Fax: +1.204.878.3980 Toll Free: +1.866.327.1957